

PRODUCT-DETAILS

3GQA131101-CDA

M2QA 132S2A



General Information

Product ID	3GQA131101-CDA
ABB Type Designation	M2QA132S2A
Catalog Description	M2QA 132S2A

Additional Information

ABB Type Designation	M2QA132S2A
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2RS/C3
Bearing NDE	6207-2RS/C3
Country of Origin	China (CN)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque
D	--	50 Hz	380-420 V	5.50 kW	2920 r/min	10.70 A	0.890	87.50 %	17.99 N·m
Y	--	50 Hz	660-690 V	5.50 kW	2920 r/min	6.18 A	0.890	87.00 %	
D	--	60 Hz	440-480 V	6.33 kW	3510 r/min	10.55 A	0.900	87.50 %	17.22 N·m

Gross Weight	65 kg
IC Class	IC411
IM Class	IMB14 IM3601

IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2QA 132S2A
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Product Main Type	M2QA 132
Product Name	3 PHASE AC MOTOR
Product Net Height	330 mm
Product Net Length	465 mm
Product Net Weight	58 kg
Product Net Width	265 mm
Product Type	QA__Cast_Iron_motor
Quote Only	No
Selling Unit of Measure	piece
Sound dB (A)	70 dB(A)
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	Product Not in WEEE Scope

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE1 Standard Efficiency Cast Iron Motors

