

PRODUCT-DETAILS

3GQA132101-BDA

M2QA 132S4A



General Information

Product ID	3GQA132101-BDA
ABB Type Designation	M2QA132S4A
Catalog Description	M2QA 132S4A

Additional Information

ABB Type Designation	M2QA132S4A
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2RS/C3
Bearing NDE	6207-2RS/C3
Core Credit	0.00
Country of Origin	China (CN)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor
D	--	50 Hz	380-420 V	5.50 kW	1440 r/min	10.99 A	0.850
Y	--	50 Hz	660-690 V	5.50 kW	1440 r/min	6.51 A	0.850
D	--	60 Hz	440-480 V	6.33 kW	1730 r/min	11.12 A	0.850

Gross Weight	70 kg
IC Class	IC411
IM Class	IMB5 IM3001

IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2QA 132S4A
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Package Level 1 Units	0 carton
Product Main Type	M2QA 132
Product Name	3 PHASE AC MOTOR
Product Net Weight	63 kg
Product Type	QA__Cast_Iron_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	Product Not in WEEE Scope

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE1 Standard Efficiency Cast Iron Motors

