


PRODUCT-DETAILS

3GQA161301-HDA

M2QA 160M2A



General Information

Product ID	3GQA161301-HDA
ABB Type Designation	M2QA160M2A
Catalog Description	M2QA 160M2A

Additional Information

ABB Type Designation	M2QA160M2A
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015220
Direction of Rotation	CW Clockwise

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed
D	--	50 Hz	380-420 V	11.00 kW	2930 r/min
Y	--	50 Hz	660-690 V	11.00 kW	2930 r/min
D	--	60 Hz	440-480 V	12.70 kW	

Gross Weight	126 kg
IC Class	IC411
IM Class	IMB35 IM2001
IP Class	IP55

Insulation Class	ICLF
Invoice Description	M2QA 160M2A
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Moment of Inertia	0.04360 kg/m³
Number of Poles (High)	2
Product Main Type	M2QA 160
Product Name	3 PHASE AC MOTOR
Product Net Weight	118 kg
Product Type	QA__Cast_Iron_motor
Quote Only	No
Selling Unit of Measure	piece
Sound dB (A)	72 dB(A)
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	Product Not in WEEE Scope

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE1 Standard Efficiency Cast Iron Motors

