


PRODUCT-DETAILS

3GQA162501-BDA

M2QA 160L4A



General Information

Product ID	3GQA162501-BDA
ABB Type Designation	M2QA160L4A
EAN	QY162501-BDA
Catalog Description	M2QA 160L4A

Additional Information

ABB Type Designation	M2QA160L4A
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309-2Z/C3
Bearing NDE	6209-2Z/C3
Core Credit	0.00
Country of Origin	China (CN)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EAN	QY162501-BDA

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor
D	--	50 Hz	380-420 V	15.00 kW	1460 r/min	28.78 A	0.850
Y	--	50 Hz	660-690 V	15.00 kW	1460 r/min	16.64 A	0.850
D	--	60 Hz	440-480 V	17.30 kW	1760 r/min	28.36 A	0.850

Gross Weight	151 kg
--------------	--------

IC Class	IC411
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2QA 160L4A
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Package Level 1 Units	0 pallet (lift)
Product Main Type	M2QA 160
Product Name	3 PHASE AC MOTOR
Product Net Weight	140 kg
Product Type	QA__Cast_Iron_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	Product Not in WEEE Scope

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE1 Standard Efficiency Cast Iron Motors

