

PRODUCT-DETAILS

3GQA252301-ADA

M2QA 250M4A



General Information

Product ID	3GQA252301-ADA
ABB Type Designation	M2QA250M4A
Catalog Description	M2QA 250M4A

Additional Information

ABB Type Designation	M2QA250M4A
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6314/C3
Bearing NDE	6214/C3
Country of Origin	China (CN)
Customs Tariff Number	85015230
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor
D	--	50 Hz	380-420 V	55.00 kW	1480 r/min	98.50 A	0.870
Y	--	50 Hz	660-690 V	55.00 kW	1477 r/min	58.70 A	0.880
D	--	60 Hz	440-480 V	63.00 kW	1477 r/min	102.00 A	0.880
D	--	50 Hz	415 V	55.00 kW	1482 r/min	95.20 A	0.860
D	--	60 Hz	440 V	63.00 kW	1779 r/min	99.70 A	0.890
Y	--	50 Hz	690 V	55.00 kW	1480 r/min	57.10 A	0.870

Gross Weight	470 kg
--------------	--------

IC Class	IC411
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2QA 250M4A
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Product Main Type	M2QA 250
Product Name	3 PHASE AC MOTOR
Product Net Weight	435 kg
Product Type	QA__Cast_Iron_motor
Quote Only	No
Replaced Product ID (OLD)	QY252301-ADA
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	Product Not in WEEE Scope

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE1 Standard Efficiency Cast Iron Motors

