


PRODUCT-DETAILS

3GQA311502-ADA

M2QA 315L2B



General Information

Product ID	3GQA311502-ADA
ABB Type Designation	M2QA315L2B
Catalog Description	M2QA 315L2B

Additional Information

ABB Type Designation	M2QA315L2B
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316/C4
Bearing NDE	6316/C4
Country of Origin	China (CN)
Customs Tariff Number	85015381
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor
D	--	50 Hz	380-420 V	200.00 kW	2978 r/min	332.00 A	0.920
Y	--	50 Hz	660-690 V	200.00 kW	2976 r/min	198.60 A	0.930
D	--	60 Hz	440-480 V	200.00 kW	2976 r/min	345.00 A	0.930
D	--	50 Hz	415 V	200.00 kW	2980 r/min	323.00 A	0.910
D	--	60 Hz	440 V	230.00 kW	3575 r/min	326.00 A	0.930
Y	--	50 Hz	690 V	200.00 kW	2978 r/min	192.50 A	0.920

Gross Volume

1 dm³

Gross Weight	1095 kg
IC Class	IC411
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2QA 315L2B
Lubrication	Regreasable
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Product Main Type	M2QA 315
Product Name	3 PHASE AC MOTOR
Product Net Height	1 cm
Product Net Length	1 cm
Product Net Weight	1015 kg
Product Net Width	1 cm
Product Type	QA__Cast_Iron_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	Product Not in WEEE Scope

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE1 Standard Efficiency Cast Iron Motors

