

PRODUCT-DETAILS

3GQA314301-ADA

M2QA 315M8A



General Information

Product ID	3GQA314301-ADA
ABB Type Designation	M2QA315M8A
Catalog Description	M2QA 315M8A

Additional Information

ABB Type Designation	M2QA315M8A
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6319/C3
Bearing NDE	6319/C3
Country of Origin	China (CN)
Customs Tariff Number	85015230
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor
D	--	50 Hz	380-420 V	75.00 kW	740 r/min	143.00 A	0.820
Y	--	50 Hz	660-690 V	75.00 kW	736 r/min	85.21 A	0.830
D	--	60 Hz	440-480 V	86.00 kW	736 r/min	148.00 A	0.830
D	--	50 Hz	415 V	75.00 kW	741 r/min	140.00 A	0.800
D	--	60 Hz	440 V	86.00 kW	888 r/min	139.00 A	0.830
Y	--	50 Hz	690 V	75.00 kW	740 r/min	82.90 A	0.820

Gross Weight	1064 kg
--------------	---------

IC Class	IC411
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2QA 315M8A
Lubrication	Regreasable
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Product Main Type	M2QA 315
Product Name	3 PHASE AC MOTOR
Product Net Weight	945 kg
Product Type	QA__Cast_Iron_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	Product Not in WEEE Scope

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE1 Standard Efficiency Cast Iron Motors

