



PRODUCT-DETAILS

3GVA072001CSKLX

No Description Available

General Information

Product ID	3GVA072001CSKLX
ABB Type Designation	M2VA 71 A-4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M2VA 71 A-4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203-2ZC3
Bearing NDE	6202-2ZC3
Country of Origin	Italy (IT)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	380-420 V	0.25 kW	1410 r/min	0.80 A	0.710	70.40 %	1.71 N-m	4.30
D	--	50 Hz	220-240 V	0.25 kW	1410 r/min	0.80 A	0.710	70.40 %	1.71 N-m	4.30
Y	--	60 Hz	440-480 V	0.30 kW	1690 r/min	1.40 A	0.740	70.40 %	1.71 N-m	4.30
D	--	60 Hz	250-280 V	0.30 kW	1690 r/min	1.40 A	0.740	70.40 %	1.71 N-m	4.30

Gross Weight	5.7 kg
IC Class	IC411
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Moment of Inertia	0.00066 kg/m ³
Number of Poles (High)	4
Output Power	0.25 kW
Package Level 1 Units	1 carton
Pre Modified Motor	3GVA072001-CSB
Product ID	

Product Name	3-Phase squirrel cage motor
Product Net Weight	5.5 kg
Product Type	M2VA
Quote Only	No
Selling Unit of Measure	piece
Sound dB (A)	45 dB(A)
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Västerås, Sweden
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → Legacy IEC Low Voltage Motors → Aluminum Motors

Motors and Generators → IEC Low Voltage AC Motors → Legacy IEC Low Voltage Motors → Marine General Purpose Motors