



PRODUCT-DETAILS

3GVA077232-CHC

No Description Available

General Information

Product ID	3GVA077232-CHC
ABB Type Designation	M3VA 71B 4/6 v
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3VA 71B 4/6 v
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203-2Z/C3
Bearing NDE	6202-2Z/C3
Country of Origin	Romania (RO)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400-415 V	0.30 kW	1400 r/min	1.00 A	0.800	56.00 %	2.05 N·m	2.80
Y	--	50 Hz	400-415 V	0.10 kW	900 r/min	0.60 A	0.600	39.00 %	1.00 N·m	2.60

Gross Weight	6.7 kg
IC Class	IC411
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Moment of Inertia	0.00089 kg/m³
Number of Poles (High)	4
Number of Poles (Low)	6
Output Power	0.30 kW
Package Level 1 Units	1 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	6.5 kg
Product Type	M2VA
Quote Only	No
Selling Unit of Measure	piece

Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Vittuone, Italy
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	Yes
Type of Duty	S1
UNSPSC	26101100
Voltage Code	H
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Legacy IEC Low Voltage Motors → Aluminum Motors

Motors and Generators → IEC Low Voltage AC Motors → Legacy IEC Low Voltage Motors → Global Motors

Motors and Generators → IEC Low Voltage AC Motors → Legacy IEC Low Voltage Motors → Marine General Purpose Motors