

PRODUCT-DETAILS

S91.3CS35

S91.3CS35 Miniature Circuit Breaker

General Information

Extended Product Type	S91.3CS35
Product ID	4TQG672494R0000
EAN	5413656724940
Catalog Description	S91.3CS35 Miniature Circuit Breaker
Long Description	S91.3CS35

Technical

Product Name	Miniature Circuit Breaker
Tripping Characteristic	CS
Rated Operational Voltage	acc. to IEC 60947-2 400 V
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Input Voltage Type	AC
Rated Current (I _n)	35 A
Rated Short-Circuit Capacity (I _{cn})	(400 V) 25 kA (230 V) 25 kA
Rated Frequency (f)	50 ... 60 Hz
Number of Poles	1
Number of Protected Poles	3
Overvoltage Category	III
Accessories Available	Yes
Number of Batteries	0
Connecting Capacity	Rigid 1 ... 35 mm ² Flexible 0.75 ... 25 mm ²

Environmental

Ambient Air Temperature	Operation -25 ... 55 °C
Degree of Protection	IP20
Pollution Degree	2

Dimensions

Width in Number of Modular Spacings	45
Product Net Width	0.125 m
Product Net Height	0.105 m
Product Net Depth / Length	0.115 m
Product Net Weight	1.067 kg
Built-In Depth (t ₂)	44 mm

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	8536303090
Country of Origin	Poland (PL)
Selling Unit of Measure	piece

Classifications

ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8536303090
Object Classification Code	Q

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → GE Legacy → MCB GE