

PRODUCT-DETAILS

DS4414FR000

400A,REC,3P4W,MG,414,3P600V



General Information

Extended Product Type	DS4414FR000
Product ID	7TAA057030R0713
EAN	0708917266174
Catalog Description	400A,REC,3P4W,MG,414,3P600V
Long Description	MaxGard Female Receptacle, 400 Amp, 3 Pole 4 Wire, 30 600V, 60Hz

Ordering

EAN	0708917266174
UPC	708917266174
Country of Origin	United States (US)
Customs Tariff Number	8536302000
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	8 in 203 mm
Package Level 1 Height	10 in 254 mm
Package Level 1 Depth / Length	10 in 254 mm

Additional Information

Application	Shore power to marine vessels-sightseeing boats
Brand / Label	Russellstoll
Current Rating	400 A
Effective Date	19970930
Material	Cast Aluminum
Number of Batteries	0
Number of Conductors	4
Number of Poles	3
Product Name	RUSSELLSTOLL
Product Type	MaxGard Interconnection Systems
Special Functions	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Voltage Rating	600 V

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	DS4414FR000
Instructions and Manuals	DS4414FR000

Classifications

ETIM 6	EC001322 - Round socket/plug for high currents
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

