

PRODUCT-DETAILS

DS6414MR00K

60A,NLT,3P4W,MG,414,00K,3P600V



General Information

Extended Product Type	DS6414MR00K
Product ID	7TAA057030R0811
EAN	0708917267690
Catalog Description	60A,NLT,3P4W,MG,414,00K,3P600V
Long Description	MaxGard Male Inlet with Control Contacts, 60 Amp, 3 Pole 4 Wire, 30 600V, 60Hz

Ordering

EAN	0708917267690
UPC	708917267690
Country of Origin	United States (US)
Customs Tariff Number	8536302000
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	4 in 102 mm
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	5.37 in 136 mm

Additional Information	
Application	Power for trade show exhibits and concerts
Brand / Label	Russellstoll
Current Rating	60 A
Effective Date	19971210
Material	Cast Aluminum
Number of Batteries	0
Number of Conductors	4
Number of Poles	3
Product Name	RUSSELLSTOLL
Product Type	MaxGard Interconnection Systems
Special Functions	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Voltage Rating	600 V

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	DS6414MR00K
Instructions and Manuals	DS6414MR00K

Classifications	
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

