

PRODUCT-DETAILS

DS6504FR00K

60A,REC,4P5W,MG,504,00K,3PY277V



General Information

Extended Product Type	DS6504FR00K
Product ID	7TAA057030R0823
EAN	0708917177234
Catalog Description	60A,REC,4P5W,MG,504,00K,3PY277V
Long Description	MaxGard Female Receptacle with Control Contacts, 60 Amp, 4 Pole 5 Wire, 30Y 277/480V, 60Hz

Ordering

EAN	0708917177234
UPC	708917177234
Country of Origin	United States (US)
Customs Tariff Number	8536100040
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	4.75 in 121 mm
Package Level 1 Height	4.63 in 118 mm
Package Level 1 Depth / Length	8.63 in 219 mm

Additional Information

Application	Power for trade show exhibits and concerts
Brand / Label	Russellstoll
Current Rating	60 A
Effective Date	19960411
Material	Cast Aluminum
Number of Batteries	0
Number of Conductors	5
Number of Poles	4
Product Name	RUSSELLSTOLL
Product Type	MaxGard Interconnection Systems
Special Functions	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Voltage Rating	277 V

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	DS6504FR00K
Instructions and Manuals	DS6504FR00K

Classifications

ETIM 6	EC001322 - Round socket/plug for high currents
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

