

PRODUCT-DETAILS

DS6507MP000

60A,PLG,4P5W,MG,3PY125/250V,SC



General Information

Extended Product Type	DS6507MP000
Product ID	7TAA057030R0835
EAN	0708917303053
Catalog Description	60A,PLG,4P5W,MG,3PY125/250V,SC
Long Description	MaxGard Male Plug, 60 Amp, 4 Pole 5 Wire, 30Y 125/250V, 60Hz

Ordering

EAN	0708917303053
UPC	708917303053
Country of Origin	United States (US)
Customs Tariff Number	8536694020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	4.25 in 108 mm
Package Level 1 Height	4.25 in 108 mm
Package Level 1 Depth / Length	10.25 in 260 mm

Additional Information

Application	Power for trade show exhibits and concerts
Brand / Label	Russellstoll
Current Rating	60 A
Effective Date	20010112
Material	Cast Aluminum
Number of Batteries	0
Number of Conductors	5
Number of Poles	4
Product Name	RUSSELLSTOLL
Product Type	MaxGard Interconnection Systems
Special Functions	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Standards	UL E68085
Voltage Rating	250 V

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	DS6507MP000
Instructions and Manuals	DS6507MP000

Classifications

ETIM 6	EC001322 - Round socket/plug for high currents
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

