

PRODUCT-DETAILS

DS6514FR000

60A,REC,4P5W,MG,514,3PY347V



General Information

Extended Product Type	DS6514FR000
Product ID	7TAA057030R0850
EAN	0708917313205
Catalog Description	60A,REC,4P5W,MG,514,3PY347V
Long Description	MaxGard Female Receptacle, 60 Amp, 4 Pole 5 Wire, 30Y 347/600V, 60Hz

Ordering

EAN	0708917313205
UPC	708917313205
Country of Origin	United States (US)
Customs Tariff Number	8536694020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	8.63 in 219 mm
Package Level 1 Height	4.63 in 118 mm
Package Level 1 Depth / Length	4.75 in 121 mm

Additional Information

Application	Power for trade show exhibits and concerts
Brand / Label	Russellstoll
Current Rating	60 A
Effective Date	20070207
Material	Cast Aluminum
Number of Batteries	0
Number of Conductors	5
Number of Poles	4
Product Name	CILYNDRICAL MULTICONTACT CONNECTOR
Product Type	MaxGard Interconnection Systems
Special Functions	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	DS6514FR000
Instructions and Manuals	DS6514FR000

Classifications

ETIM 6	EC001322 - Round socket/plug for high currents
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

