

PRODUCT-DETAILS

DS6517MP000

60A,NLT,4P5W,MG,3PY120/208V,400HZ



General Information

Extended Product Type	DS6517MP000
Product ID	7TAA057030R0864
EAN	0708917403579
Catalog Description	60A,NLT,4P5W,MG,3PY120/208V,400HZ
Long Description	MaxGard Male Plug, 60 Amp, 4 Pole 5 Wire, 30 120/208V, 400Hz

Ordering

EAN	0708917403579
UPC	708917403579
Country of Origin	United States (US)
Customs Tariff Number	8536694020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	350 in 8890 mm
Package Level 1 Height	350 in 8890 mm
Package Level 1 Depth / Length	913 in 23190 mm

Additional Information

Application	Power for trade show exhibits and concerts
Brand / Label	Russellstoll
Current Rating	60 A
Effective Date	19990922
Material	Cast Aluminum
Number of Batteries	0
Number of Conductors	5
Number of Poles	4
Product Name	RUSSELLSTOLL
Product Type	MaxGard Interconnection Systems
Special Functions	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Standards	UL E68085
Voltage Rating	208 V

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	DS6517MP000
Instructions and Manuals	DS6517MP000

Classifications

ETIM 6	EC001322 - Round socket/plug for high currents
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

