

PRODUCT-DETAILS

DSE3207FR0

30A,REC,2P3W,MG,207,250V,SC,XP



General Information

Extended Product Type	DSE3207FR0
Product ID	7TAA057030R0873
EAN	0708917302391
Catalog Description	30A,REC,2P3W,MG,207,250V,SC,XP
Long Description	MaxGard Explosion-Proof Non-Interlocked Receptacle, 30 Amp, 2 Pole 3 Wire, 250V, 60Hz

Ordering

EAN	0708917302391
UPC	708917302391
Country of Origin	United States (US)
Customs Tariff Number	8536694020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	11.13 in 283 mm
Package Level 1 Height	13.13 in 334 mm
Package Level 1 Depth / Length	13.75 in 349 mm

Additional Information	
Application	Power for trade show exhibits and concerts, Electrical hook-up of mobile medical imging (MMI trailers)
Brand / Label	Russellstoll
Effective Date	20000925
Material	Cast Aluminum
Number of Batteries	0
Product Name	RUSSELLSTOLL
Product Type	Russellstoll Hazardous Locations
Special Functions	Explosion-proof waterproof non-interlocked receptacle O-ring sealed along with optional control contacts fully UL listed.
Standards	UL E10919

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	DSE3207FR0
Instructions and Manuals	DSE3207FR0

Classifications	
ETIM 6	EC001322 - Round socket/plug for high currents
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121406
IDEA Granular Category Code (IGCC)	4536 >> Electrical receptacles

Categories
Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

