

PRODUCT-DETAILS

DSE3216FR0

60A,REC,2P3W,MG,216,208V,XP



General Information

Extended Product Type	DSE3216FR0
Product ID	7TAA057030R0874
EAN	0708917297642
Catalog Description	60A,REC,2P3W,MG,216,208V,XP
Long Description	Maxgard Explosion-Proof Non-Interlocked Receptacle, 30Amp, 2 Pole 3 Wire, 208V, 60Hz

Ordering

EAN	0708917297642
UPC	708917297642
Country of Origin	United States (US)
Customs Tariff Number	8536694020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	11.13 in 283 mm
Package Level 1 Height	13.13 in 334 mm
Package Level 1 Depth / Length	13.75 in 349 mm

Additional Information	
Brand / Label	Russellstoll
Current Rating	30 A
Effective Date	19981123
Number of Batteries	0
Number of Conductors	3
Number of Poles	2
Product Name	RUSSELLSTOLL
Standards	UL e10919
Voltage Rating	208 V

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	DSE3216FR0
Instructions and Manuals	DSE3216FR0

Classifications	
ETIM 6	EC001322 - Round socket/plug for high currents
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

