

PRODUCT-DETAILS

DSE3404FRK

30A,REC,3P4W,MG,404,3P480,XP,SC,CC



General Information

Extended Product Type	DSE3404FRK
Product ID	7TAA057030R0875
EAN	0708917264552
Catalog Description	30A,REC,3P4W,MG,404,3P480,XP,SC,CC
Long Description	MaxGard Explosion-Proof Non-Interlocked Receptacle with Control Contacts, 30 Amp, 3 Pole 4 Wire, 30 480V, 60Hz

Ordering

EAN	0708917264552
UPC	708917264552
Country of Origin	United States (US)
Customs Tariff Number	8537109170
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	11.13 in 283 mm
Package Level 1 Height	13.13 in 334 mm
Package Level 1 Depth / Length	13.75 in 349 mm

Additional Information	
Application	Power for trade show exhibits and concerts, Electrical hook-up of mobile medical imaging (MMI trailers)
Brand / Label	Russellstoll
Current Rating	30 A
Effective Date	19970718
Material	Cast Aluminum
Number of Batteries	0
Number of Conductors	4
Number of Poles	3
Product Name	RUSSELLSTOLL
Product Type	Russellstoll Hazardous Locations
Special Functions	Explosion-proof waterproof non-interlocked receptacle O-ring sealed along with optional control contacts fully UL listed.
Standards	UL E10919
Voltage Rating	480 V

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	DSE3404FRK
Instructions and Manuals	DSE3404FRK

Classifications	
ETIM 6	EC001322 - Round socket/plug for high currents
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories
Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

