

## PRODUCT-DETAILS

# DSE3416FR0

30A,REC,3P4W,MG,416,3P208V,XP,SC



## General Information

|                       |                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------|
| Extended Product Type | DSE3416FR0                                                                               |
| Product ID            | 7TAA057030R0880                                                                          |
| EAN                   | 0708917183730                                                                            |
| Catalog Description   | 30A,REC,3P4W,MG,416,3P208V,XP,SC                                                         |
| Long Description      | Maxgard Explosion-Proof Non-Interlocked Receptacle, 30 Amp, 3 Pole 4 Wire, 30 208V, 60Hz |

## Ordering

|                         |                    |
|-------------------------|--------------------|
| EAN                     | 0708917183730      |
| UPC                     | 708917183730       |
| Country of Origin       | United States (US) |
| Customs Tariff Number   | 8536100040         |
| Selling Unit of Measure | each               |

## Container Information

|                                |                    |
|--------------------------------|--------------------|
| Package Level 1 Units          | 1 piece            |
| Package Level 1 Width          | 11.13 in<br>283 mm |
| Package Level 1 Height         | 13.13 in<br>334 mm |
| Package Level 1 Depth / Length | 13.75 in<br>349 mm |

| Additional Information |              |
|------------------------|--------------|
| Brand / Label          | Russellstoll |
| Current Rating         | 30 A         |
| Effective Date         | 19960411     |
| Number of Batteries    | 0            |
| Number of Conductors   | 4            |
| Number of Poles        | 3            |
| Product Name           | RUSSELLSTOLL |
| Standards              | UL e10919    |
| Voltage Rating         | 208 V        |

| Certificates and Declarations (Document Number) |            |
|-------------------------------------------------|------------|
| Data Sheet, Technical Information               | DSE3416FR0 |
| Instructions and Manuals                        | DSE3416FR0 |

| Classifications                    |                                                |
|------------------------------------|------------------------------------------------|
| ETIM 6                             | EC001322 - Round socket/plug for high currents |
| ETIM 7                             | EC001322 - Round socket/plug for high currents |
| ETIM 8                             | EC001322 - Round socket/plug for high currents |
| UNSPSC                             | 39121404                                       |
| IDEA Granular Category Code (IGCC) | 4528 >> Electrical sleeves                     |

## Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

