

PRODUCT-DETAILS

DSE3516FRK

30A,REC,4P5W,MG,516,3PY208,XP,CC



General Information

Extended Product Type	DSE3516FRK
Product ID	7TAA057030R0884
EAN	0708917140184
Catalog Description	30A,REC,4P5W,MG,516,3PY208,XP,CC
Long Description	MaxGard Explosion-Proof Non-Interlocked Receptacle with Control Contacts, 30 Amp, 4 Pole 5 Wire, 3 Phase Y 208 Volt

Ordering

EAN	0708917140184
UPC	708917140184
Country of Origin	United States (US)
Customs Tariff Number	8536100040
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	11.13 in 283 mm
Package Level 1 Height	13.13 in 334 mm
Package Level 1 Depth / Length	13.75 in 349 mm

Additional Information	
Brand / Label	Russellstoll
Current Rating	30 A
Effective Date	19960411
Number of Batteries	0
Number of Conductors	5
Number of Poles	4
Product Name	RUSSELLSTOLL
Standards	UL e10919
Voltage Rating	208 V

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	DSE3516FRK
Instructions and Manuals	DSE3516FRK

Classifications	
ETIM 6	EC001322 - Round socket/plug for high currents
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

