

## PRODUCT-DETAILS

# DS4414FRABK

400A,REC,3P4W,MG,414,ABK,3P600V



## General Information

|                       |                                                                                                                        |
|-----------------------|------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | DS4414FRABK                                                                                                            |
| Product ID            | 7TAA057980R0807                                                                                                        |
| EAN                   | 0708917310204                                                                                                          |
| Catalog Description   | 400A,REC,3P4W,MG,414,ABK,3P600V                                                                                        |
| Long Description      | MaxGard Female Receptacle with Angle Adapter, Junction Box and Control Contacts, 400 Amp, 3 Pole 4 Wire, 30 600V, 60Hz |

## Ordering

|                         |                    |
|-------------------------|--------------------|
| EAN                     | 0708917310204      |
| UPC                     | 708917310204       |
| Country of Origin       | United States (US) |
| Customs Tariff Number   | 8536694020         |
| Selling Unit of Measure | each               |

## Container Information

|                                |                    |
|--------------------------------|--------------------|
| Package Level 1 Units          | 1 piece            |
| Package Level 1 Width          | 15.38 in<br>391 mm |
| Package Level 1 Height         | 15.69 in<br>399 mm |
| Package Level 1 Depth / Length | 26.25 in<br>667 mm |

## Additional Information

|                      |                                                                                                                                                                  |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Application          | Shore power to marine vessels-sightseeing boats                                                                                                                  |
| Brand / Label        | Russellstoll                                                                                                                                                     |
| Current Rating       | 400 A                                                                                                                                                            |
| Effective Date       | 20040602                                                                                                                                                         |
| Material             | Cast Aluminum                                                                                                                                                    |
| Number of Batteries  | 0                                                                                                                                                                |
| Number of Conductors | 4                                                                                                                                                                |
| Number of Poles      | 3                                                                                                                                                                |
| Product Name         | 400A RECEPTACLE 3P4W 3P 600V                                                                                                                                     |
| Product Type         | MaxGard Interconnection Systems                                                                                                                                  |
| Special Functions    | Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight"). |
| Voltage Rating       | 600 V                                                                                                                                                            |

## Certificates and Declarations (Document Number)

|                                   |             |
|-----------------------------------|-------------|
| Data Sheet, Technical Information | DS4414FRABK |
| Instructions and Manuals          | DS4414FRABK |

## Classifications

|                                    |                                                |
|------------------------------------|------------------------------------------------|
| ETIM 6                             | EC001322 - Round socket/plug for high currents |
| ETIM 7                             | EC001322 - Round socket/plug for high currents |
| ETIM 8                             | EC001322 - Round socket/plug for high currents |
| UNSPSC                             | 39121404                                       |
| IDEA Granular Category Code (IGCC) | 4528 >> Electrical sleeves                     |

## Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

