

PRODUCT-DETAILS

DS6316FR000

60A,REC,3P4W,MG,316,120/208V



General Information

Extended Product Type	DS6316FR000
Product ID	7TAA057980R0836
EAN	0708917209256
Catalog Description	60A,REC,3P4W,MG,316,120/208V
Long Description	MaxGard Female Receptacle, 60 Amp, 3 Pole 4 Wire, 120/208V, 60Hz

Ordering

EAN	0708917209256
UPC	708917209256
Country of Origin	United States (US)
Customs Tariff Number	8536100040
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	4.75 in 121 mm
Package Level 1 Height	4.63 in 118 mm
Package Level 1 Depth / Length	8.63 in 219 mm

Additional Information		
Application	Power for trade show exhibits and concerts	
Brand / Label	Russellstoll	
Current Rating	60 A	
Effective Date	19960411	
Material	Cast Aluminum	
Number of Batteries	0	
Number of Conductors	4	
Number of Poles	3	
Product Name	RUSSELLSTOLL	
Product Type	MaxGard Interconnection Systems	
Special Functions	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").	
Voltage Rating	208 V	

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	DS6316FR000
Instructions and Manuals	DS6316FR000

Classifications	
ETIM 6	EC001322 - Round socket/plug for high currents
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories
Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

