

PRODUCT-DETAILS

DSE3404FR0

30A,REC,3P4W,MG,404,3P480V,XP



General Information

Extended Product Type	DSE3404FR0
Product ID	7TAA057980R0873
EAN	0708917268376
Catalog Description	30A,REC,3P4W,MG,404,3P480V,XP
Long Description	Maxgard Explosion-Proof Non-Interlocked Receptacle, 30 Amp, 3 Pole 4 Wire, 30 480V, 60Hz

Ordering

EAN	0708917268376
UPC	708917268376
Country of Origin	United States (US)
Customs Tariff Number	8536694020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	11.13 in 283 mm
Package Level 1 Height	13.13 in 334 mm
Package Level 1 Depth / Length	13.75 in 349 mm

Additional Information	
Brand / Label	Russellstoll
Current Rating	30 A
Effective Date	19980106
Number of Batteries	0
Number of Conductors	4
Number of Phases	Three
Number of Poles	3
Product Name	RUSSELLSTOLL
Standards	UL E10919
Voltage Rating	480 V

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	DSE3404FR0
Instructions and Manuals	DSE3404FR0

Classifications	
ETIM 6	EC001322 - Round socket/plug for high currents
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121406
IDEA Granular Category Code (IGCC)	4536 >> Electrical receptacles

Categories
Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

