

PRODUCT-DETAILS

DSRS6504NA000

60A,ILK,4P5W,MG,3PY277V,NONAUTO



General Information

Extended Product Type	DSRS6504NA000
Product ID	7TAA057980R0898
EAN	0708917310914
Catalog Description	60A,ILK,4P5W,MG,3PY277V,NONAUTO
Long Description	MaxGard Interlocked Receptacle with Non-Automatic Breaker and Screw Cap, 60 Amp, 4 Pole 5 Wire, 30Y 277/480V, 60Hz

Ordering

EAN	0708917310914
UPC	708917310914
Country of Origin	United States (US)
Customs Tariff Number	8537109170
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	13 in 330 mm
Package Level 1 Height	11.13 in 283 mm
Package Level 1 Depth / Length	24 in 610 mm

Additional Information

Application	Power for trade show exhibits and concerts, Electrical hook-up of mobile medical imaging (MMI trailers)
Brand / Label	Russellstoll
Current Rating	60 A
Effective Date	20041027
Material	Cast Aluminum
Number of Batteries	0
Number of Conductors	5
Number of Poles	4
Product Name	ELECTRICAL BASE
Product Type	MaxGard Interconnection Systems
Special Functions	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Voltage Rating	277 V

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	DSRS6504NA000
Instructions and Manuals	DSRS6504NA000

Classifications

ETIM 6	EC001322 - Round socket/plug for high currents
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

