

PRODUCT-DETAILS

03700220

600A 1H ALCOMPR LUG No2 STR No1 SOL



General Information

Extended Product Type	03700220
Product ID	7TAA122010R0002
EAN	0783786657421
Catalog Description	600A 1H ALCOMPR LUG No2 STR No1 SOL
Long Description	15/25/35kV 600 Amp Series Deadbreak Compression Lug (Tin-Plated Aluminum). Conductor Size AWG Compressed/Stranded #2, or Compacted/Solid #1. Length 5.94 inches. Diameter 1.38 Inches. 1-Hole Pad, .50 inch Thick. Hole Size .688 inch Diameter.

Ordering

EAN	0783786657421
UPC	783786657421
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	2 in 51 mm
Package Level 1 Height	2 in 51 mm
Package Level 1 Depth /	7 in

Length 178 mm

Additional Information

Application	Used with 15/25/35kV 600 Amp Deadbreak Elbow and Splice products.
Brand / Label	Elastimold
Cable Size	#2 STR AWG #2 COMPR AWG
Color	Silver
Connection Type	Compression
Current Rating	600 A
Effective Date	19980115
Insulation Material	None
Material	Aluminum
Number of Batteries	0
Product Name	"ELECTRICAL CONNECTOR,>1000V"
Product Type	Compression Lug
Size	Length 5.94 inch, Diameter 1.38 inch, Hole .688 inch Diameter.
Special Functions	Tin Plated Aluminum. Hole Size .688 inch. Connectors can used with both Copper and Aluminum Conductors.
Voltage Rating	15 to 35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	03700220
Instructions and Manuals	03700220

Classifications

ETIM 6	EC001053 - Crimp cable lug for aluminium conductors
ETIM 7	EC001053 - Crimp cable lug for aluminium conductors
ETIM 8	EC001053 - Crimp cable lug for aluminium conductors
UNSPSC	39121405
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4532 >> Cable or wire lug

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

