

## PRODUCT-DETAILS

# 755L2-M0300-S

## 35KV 600A DB 2-WAY L-KIT M0300-SEAL



### General Information

|                       |                                                                                                                                                                                                                                                                               |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 755L2-M0300-S                                                                                                                                                                                                                                                                 |
| Product ID            | 7TAA122370R0006                                                                                                                                                                                                                                                               |
| EAN                   | 0783786418442                                                                                                                                                                                                                                                                 |
| Catalog Description   | 35KV 600A DB 2-WAY L-KIT M0300-SEAL                                                                                                                                                                                                                                           |
| Long Description      | 600 Amp, DeadBreak Elbow Connector, 2-Way L Kit, 35KV, Cable Insulation Diameter 1.370 inch to 1.630 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 350 / Compacted Solid 400 /mmSquared Compact 185. Cold-Shrinkable Jacket Seal Included. |

### Ordering

|                         |                    |
|-------------------------|--------------------|
| EAN                     | 0783786418442      |
| UPC                     | 783786418442       |
| Country of Origin       | United States (US) |
| Customs Tariff Number   | 8535908020         |
| Selling Unit of Measure | each               |

### Container Information

|                        |               |
|------------------------|---------------|
| Package Level 1 Units  | 1 piece       |
| Package Level 1 Width  | 1 in<br>25 mm |
| Package Level 1 Height | 1 in<br>25 mm |

Package Level 1 Depth /  
Length

1 in  
25 mm

## Additional Information

|                          |                                                                                                                                                                                                  |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Application              | Used to connect two cable ends and using the two insulating plugs as test points allows for capacitive voltage testing                                                                           |
| Brand / Label            | Elastimold                                                                                                                                                                                       |
| Color                    | Black                                                                                                                                                                                            |
| Connection Type          | Compression                                                                                                                                                                                      |
| Current Rating           | 600 A                                                                                                                                                                                            |
| Effective Date           | 20040107                                                                                                                                                                                         |
| Environmental Conditions | Fully Submersible                                                                                                                                                                                |
| Includes                 | (2) Elbows, (2) Cable Size Adapters, (2) Compression Lugs, (6) Tubes of Lubricant, (2) Basic Insulating Plugs with Caps, (2) Studs, (1) Connecting Plug, Installation Instructions, Crimp Chart. |
| Insulation Material      | Yes, EPDM Rubber                                                                                                                                                                                 |
| Material                 | Housing - EPDM Rubber                                                                                                                                                                            |
| Number of Batteries      | 0                                                                                                                                                                                                |
| Product Name             | ELECTRICAL CONNECTOR,>1000V                                                                                                                                                                      |
| Product Type             | Deadbreak 2-Way L Kit                                                                                                                                                                            |
| Size                     | 25.38 inch Wide, 13.93 inch from Bottom of T to Center of Plug.                                                                                                                                  |
| Special Functions        | Cold-Shrinkable Jacket Seal                                                                                                                                                                      |
| Standards                | ANSI/IEEE Standard 386                                                                                                                                                                           |
| Temperature Range        | -40 to +65 °C                                                                                                                                                                                    |
| Voltage Rating           | 35 kV                                                                                                                                                                                            |

## Certificates and Declarations (Document Number)

|                                   |               |
|-----------------------------------|---------------|
| Data Sheet, Technical Information | 755L2-M0300-S |
| Instructions and Manuals          | 755L2-M0300-S |

## Classifications

|                                    |                                       |
|------------------------------------|---------------------------------------|
| UNSPSC                             | 39121421                              |
| WEEE Category                      | Product Not in WEEE Scope             |
| IDEA Granular Category Code (IGCC) | 4586 >> Electrical connector assembly |

## Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

