

## PRODUCT-DETAILS

# 755LRTP-P0380-DRG

## 35kv 600/200A S-OP LB W/TP P0380DRG



### General Information

|                       |                                                                                                                                                                                                                                                          |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 755LRTP-P0380-DRG                                                                                                                                                                                                                                        |
| Product ID            | 7TAA122400R0091                                                                                                                                                                                                                                          |
| EAN                   | 0783786407118                                                                                                                                                                                                                                            |
| Catalog Description   | 35kv 600/200A S-OP LB W/TP P0380DRG                                                                                                                                                                                                                      |
| Long Description      | 600 Amp, 35KV, Stick Op Connector Kit with Test Point, Insulated Cap and Reducing Tap Plug. Cable Insulation Diameter 1.725 inch to 1.935 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 700/750 /Compacted Solid 900. |

### Ordering

|                         |                    |
|-------------------------|--------------------|
| EAN                     | 0783786407118      |
| UPC                     | 783786407118       |
| Country of Origin       | United States (US) |
| Customs Tariff Number   | 8535908020         |
| Selling Unit of Measure | each               |

### Container Information

|                        |               |
|------------------------|---------------|
| Package Level 1 Units  | 1 piece       |
| Package Level 1 Width  | 1 in<br>25 mm |
| Package Level 1 Height | 1 in<br>25 mm |

Package Level 1 Depth /  
Length

1 in  
25 mm

## Additional Information

|                          |                                                                                                                                                                                                                                                          |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Application              | Mates with a 600 Amp elbow interface and provides a 200 Amp load break tap, an access hole thru the bore of the reducing tap plug allows use of a 600AT operating tool to bolt and secure the component to a mating 600 Amp elbow and apparatus bushing. |
| Brand / Label            | Elastimold                                                                                                                                                                                                                                               |
| Color                    | Black                                                                                                                                                                                                                                                    |
| Current Rating           | 600 to 200 A                                                                                                                                                                                                                                             |
| Effective Date           | 20030717                                                                                                                                                                                                                                                 |
| Environmental Conditions | Fully Submersible                                                                                                                                                                                                                                        |
| Includes                 | Elbow Housing, Reducing Tap Plug, Insulated Cap, Cable Size Adapter, Compression Lug, Lubricant, Instruction Sheet, Crimp Chart.                                                                                                                         |
| Insulation Material      | Yes, EPDM Rubber                                                                                                                                                                                                                                         |
| Material                 | Housing - EPDM Rubber                                                                                                                                                                                                                                    |
| Number of Batteries      | 0                                                                                                                                                                                                                                                        |
| Product Name             | ELECTRICAL CONNECTOR,>1000V                                                                                                                                                                                                                              |
| Product Type             | Stick-OP Elbow Connector                                                                                                                                                                                                                                 |
| Size                     | Cable Insulation Diameter 1.725 inch to 1.935 inch.                                                                                                                                                                                                      |
| Special Functions        | Test Point. 35kV Reducing Tap Plug. Includes Hex-Broach for Torque Installation. Peroxide-Cured Insulation and Jacket.                                                                                                                                   |
| Standards                | ANSI/IEEE Standard 386                                                                                                                                                                                                                                   |
| Temperature Range        | -40 to +65 °C                                                                                                                                                                                                                                            |
| Voltage Rating           | 35 kV                                                                                                                                                                                                                                                    |

## Certificates and Declarations (Document Number)

|                                   |                   |
|-----------------------------------|-------------------|
| Data Sheet, Technical Information | 755LRTP-P0380-DRG |
| Instructions and Manuals          | 755LRTP-P0380-DRG |

## Classifications

|                                    |                                       |
|------------------------------------|---------------------------------------|
| UNSPSC                             | 39121421                              |
| WEEE Category                      | Product Not in WEEE Scope             |
| IDEA Granular Category Code (IGCC) | 4586 >> Electrical connector assembly |

## Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

