

## PRODUCT-DETAILS

# 15520X

## 12 or 14 TON DIE CODE 21X RED



### General Information

|                       |                                                                                                                                                                     |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 15520X                                                                                                                                                              |
| Product ID            | 7TAA131890R0022                                                                                                                                                     |
| EAN                   | 0786209923523                                                                                                                                                       |
| Catalog Description   | 12 or 14 TON DIE CODE 21X RED                                                                                                                                       |
| Long Description      | 12 or 14 Ton Hex Flex Die for Crimping Flex Conductors, 21X Die Code, Red Die Color.<br>High Grade Tool Steel. To use with 15 Ton Tool please buy adaptor 15500-TB. |

### Ordering

|                              |                 |
|------------------------------|-----------------|
| EAN                          | 0786209923523   |
| UPC                          | 786209923523    |
| Replacement Product ID (NEW) | 7TAA131880R0033 |
| Country of Origin            | Italy (IT)      |
| Customs Tariff Number        | 8207306092      |
| Selling Unit of Measure      | each            |

### Container Information

|                        |                   |
|------------------------|-------------------|
| Package Level 1 Units  | 1 piece           |
| Package Level 1 Width  | 0.75 in<br>19 mm  |
| Package Level 1 Height | 4.87 in<br>124 mm |

|                                |                   |
|--------------------------------|-------------------|
| Package Level 1 Depth / Length | 4.87 in<br>124 mm |
|--------------------------------|-------------------|

Additional Information

|                     |                       |
|---------------------|-----------------------|
| Brand / Label       | Application Tooling   |
| Capacity Rating     | 14 ton (UK)           |
| Color               | Red                   |
| Effective Date      | 20090204              |
| Material            | Steel                 |
| Number of Batteries | 0                     |
| Product Name        | DIE FOR CRIMPING TOOL |
| Product Type        | Die                   |

Certificates and Declarations (Document Number)

|                                   |        |
|-----------------------------------|--------|
| Data Sheet, Technical Information | 15520X |
| Instructions and Manuals          | 15520X |

Classifications

|                                    |                                                                                   |
|------------------------------------|-----------------------------------------------------------------------------------|
| ETIM 6                             | EC001282 - Insert for crimp tool cable lugs, cable end sleeves, screen connection |
| ETIM 7                             | EC001282 - Insert for crimp tool cable lugs, cable end sleeves, screen connection |
| UNSPSC                             | 27112820                                                                          |
| WEEE Category                      | Product Not in WEEE Scope                                                         |
| IDEA Granular Category Code (IGCC) | 2427 >> Lug crimping tool dies                                                    |

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → WMC Tools

